



1. CABLE EXAMPLES AND WIRE TIES ARE NOT SHOWN IN TOP VIEW OR RIGHT END VIEW.
2. HARDWARE IS NOT INCLUDED WITH ARMS. (i.e. ANCHORS, WASHERS, CAP SCREWS, AND WIRE TIES ARE SOLD SEPARATELY.)



SCALE:



1.000



ITEM NUMBER	CATALOG NUMBER	DESCRIPTION	QUANTITY REQUIRED PER ARM
①	FSRM-12	1/2"-13 DROP-IN ANCHOR Material: 303 STAINLESS STEEL	2
②	FFW316-17-038	FLAT WASHER ID=.531, OD=1.188, THK=.135 Material: 316 STAINLESS STEEL	2
③	FHC316-16-056	1/2"-13 X 1-3/4" LG. HEX HEAD CAP SCREW Material: 316 STAINLESS STEEL	2
④	MM10-5	MM10-5 ARM Material: Glass Reinforced Nylon	1
⑤	FRT-112	SETTING TOOL (Use To Install Catalog No. FSRM-12 Drop-in Anchor)	AS REQ'D

1. INSTALL DROP-IN ANCHORS AS SHOWN IN THIS DRAWING AND AS DESCRIBED BELOW:
 - A. DRILL 5/8" DIAMETER HOLES 2" DEEP.
 - B. BLOW OUT HOLES.
 - C. DRIVE ANCHORS FLUSH WITH THE SURFACE OF CONCRETE.
 - D. EXPAND ANCHORS WITH FRT-112 SETTING TOOL. THE ANCHOR IS PROPERLY EXPANDED WHEN SHOULDER OF SETTING TOOL IS FLUSH WITH THE TOP OF ANCHOR.
2. INSTALL FLAT WASHERS AND TIGHTEN CAP SCREWS JUST ENOUGH TO ATTAIN A SNUG FIT. AVOID HIGH SCREW TORQUE WHICH INDUCES COMPRESSIVE STRESS.

1. UNDERGROUND DEVICES, INC. TYPE 316 STAINLESS STEEL CAP SCREWS CONFORM TO ASTM F593G316.
2. "F593G316" AND THE MANUFACTURER'S IDENTIFICATION IS STAMPED ON THE HEAD OF EACH CAP SCREW.
3. "316" IS STAMPED ON ONE SIDE OF EVERY UNDERGROUND DEVICES, INC. TYPE 316 STAINLESS STEEL WASHER.
4. TYPE 316 STAINLESS STEEL CAP SCREWS AND WASHERS ARE MORE CORROSION RESISTANT THAN TYPE 18-8 STAINLESS STEEL.
5. TYPE 316 STAINLESS STEEL IS NON-MAGNETIC.

SCALE: See At Left	DESIGNED BY: Don McCoy	DETAILED BY: S Wendland	CHECKED BY: Don McCoy
DATE: 8-12-24	APPROVED BY:	REVISION:	

UNDERGROUND DEVICES, INC.
NORTHBROOK, ILLINOIS 60062 - PHONE: (847) 205-9000

DRAWING NUMBER:
90-14406
PAGE 1 OF 1